

LGe06 / LGe12



Entry level line printers for the DEC Compaq environment

The LGe range of products from TallyGenicom combines high performance, up to 1200 lines per minute, with an impressive range of ergonomic features.

Ideal for the DEC /Compaq print environment these products perform well with DEC VAX/VMS/Open VMS, with a suite of emulations which include full DEC PPL2 command set, DEC ANSI character sets and barcodes.

Automatic head gap adjustment minimises operator errors. Barcodes are always clear and crisp with high throughput using TG's patented Read/Right print algorithm. Another patent, the 'stay black' ribbons (available on LGe12 only) offer clean-hands cartridge convenience while delivering new ribbon quality over their entire 250 million character life-the longest life ribbons in the industry.

Mono Laser
Colour Laser
Production Ink
Dot Matrix
Line Matrix
Consumables

- Print speeds of 600 and 1200 lines per minute with workload up to 345,000 pages per month.
- Designed for DEC / Compaq print environments. Full support for PPL2 command set, fonts and barcodes.
- For text and barcode printing with Read/Right Algorithm, QMS Code V and PGL.
- Quick change, clean hands, long life cartridge ribbons. Up to 250 million characters with "stay black" feature (LGe12 only).
- Very low running costs.
- Serial RS232 and Parallel interfaces standard. Ethernet 10/100BaseT option. MMJ adapter included.

LGe06 / LGe12

Features & Specifications

Line Matrix Printer

Printing Technology	Line impact dot matrix		
Print speed		LGe06	LGe12
Lines per minute		Upper Case / Lower Case	Upper Case / Lower Case
	Draft	600 / 514	1200 / 1028
	DP	450 / 360	900 / 720
	Courier/Gothic	189 / 144	378 / 288
	OCR-A	360 / 276	720 / 553
	OCR-B	133 / 92	266 / 194
Graphics speed	LGe06: Up to 75 inches per minute, 50 inches per minute at 60 x 72 dots per inch LGe12: Up to 150 inches per minute, 100 inches per minute at 60 x 72 dots per inch		
Monthly Workload	LGe06: 175,000 pages per month LGe12: 345,000 pages per month		
Character pitch	13 pitches, ranging from 5 to 20 cpi Constant density and enhanced density modes		
Line pitch	1.5, 2, 3, 4, 5, 6, 7,8, 9 and 10cpi		
Graphics resolution	Up to 240 x 288dpi		
Graphics languages	QMS Code V, Printronix Graphics Language (PGL), Tally IG, DEC ANSI PPL2		
Fonts	Draft, Data Processing, Gothic,Courier, OCR-A*, OCR-B*, DEC ANSI PPL2 font set		
Barcodes	Code 39, 2/5 Matrix, 2/5 interleaved, EAN 8,EAN 13, EAN128, UPC-A, PDF417 2 dimensional, UK Post Office, with read/right algorithm, DEC ANSI PPL2		
Paper handling	2 tractors 36 inch per second (fast slew) 25 inches per second (default slew) Paper motion detection, paper out detection		
Paper sizes	Width: 2.5 to 17.25 inches Length: 1 to 255 lines		
Paper weight	65 to 365gsm		
Multi-part stationery	Up to 6 part forms Automatic Gap Adjustment Maximum forms thickness 0.025 inches		
Ribbon	LGe06: 40 million characters (standard cartridge), LGe12: 40 million (standard cartridge), 60 and 250 million characters (stay black cartridge)		
Emulations	Tally ANSI, Genciom ANSI, DEC LG01, Printronix P600 and P5000/P6000, HP 2564C, Epson FX1180, IBM proprinter III XL, MTPL, DEC ANSI PPL2		
Interfaces - Standard	IEEE 1284 compliant parallel. Serial RS232 with 38.4K baud transfer. Includes MMJ Adapter		
Network administration	TGNetAdmin for single and multiple device configuration and monitor		
Noise level	55db(A)		
Power supply	Auto ranging: 90-264V Frequency 47-63Hz		
Power consumption	105W average		
Weight	Table Top version 53Kg Pedestal version 73Kg		
Dimensions	Table Top version 330(h) x 720(w) x 442(d)mm Depth with paper exit guides assembly 595mm Pedestal mounted version 1010 (h) x 720 (w) x 595 (d)mm Depth with paper exit guides assembly 650mm Depth with paper tray 810mm		



NB: Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

* For OCR applications it is recommended that your readers are tested with print samples supplied by TallyGenicom prior to purchase.



Rutherford Road, Basingstoke,
Hampshire, RG24 8PD.
Tel: UK 0800 652 4557
International: +44 (0) 1256 481 521
Fax: UK 0870 872 2889
Web: www.tallygenicom.co.uk