

T6215



A ground breaking solution for high volume printing

The T6215 is TallyGenicom's most popular high speed line printer. Fast slewing supplements the 1500 lines per minute, resulting in paper moving through the printer faster, significantly enhancing throughput.

A model in the 'Enterprise' range, it features the patented 'Stay Black' ribbon, with consistent output quality. A first class barcode printer, it has clear advantage in speed and clarity printing dark-barcodes, thanks to a patented 'Read/Right' algorithm.

Like all 'Enterprise' series products it's optimized for Windows printing, with high throughput even for graphically rendered fonts. Durability is an important feature of TallyGenicom brand line printers. Parts are relatively inexpensive and available for many years, giving long life and contributing to the very low total running cost.

- 1500 lines per minute with 430,000 pages per month
- Designed for Windows, UNIX, DOS, SAP-R3, HP-3000 / HP-9000, AS400/iSeries, Mainframe, Legacy systems
- For text and barcode printing with Read/Right Algorithm, QMS Code V and PGL
- Quick change, clean hands, long life cartridge ribbons with "stay black" feature
- Very low running costs
- Wide range of models including:
 - Serial/Parallel
 - FourPlex (IBM Coax / Twinax)
 - LANPlex (Ethernet 10/100BaseT)
 - IPDS (LANPlex or FourPlex)
 - HP Line Jet
 - Arabic

T6215

Line Matrix Printer

Features & Specifications

Printing Technology	Line impact dot matrix		
Print speed		Upper Case (lines per minute)	Lower Case (lines per minute)
	Draft	1500	1285
	DP	1125	900
	Courier/Gothic	600	500
	OCR-A	600	500
	OCR-B	400	315
Graphics speed	Up to 187 inches per minute		
Monthly Workload	430,000 pages		
Character pitch	13 pitches, ranging from 5 to 20 cpi Constant density and enhanced density modes		
Line pitch	1.5, 2, 3, 4, 5, 6, 7, 8, 9 and 10cpi		
Graphics resolution	Up to 240 x 288dpi		
Graphics languages	QMS Code V, Printronix Graphics Language (PGL), Tally IG		
Fonts	Draft, Data Processing, Gothic, Courier, OCR-A, OCR-B, range of Arabic		
Barcodes	Code 39, 2/5 Matrix, 2/5 interleaved, EAN 8, EAN 13, EAN128, UPC-A, PDF417 2 dimensional, KIX, UK Post Office, with read/right algorithm		
Paper handling	4 tractors 36 inch per second slew rate (maximum) Paper motion detection, paper out detection		
Paper sizes	Width: 2.5 to 17.25 inches Length: 1 to 255 lines		
Paper weight	65 to 365gsm		
Multi-part stationery	Up to 6 part forms Maximum forms thickness 0.025 inches		
Ribbon life	40, 60 and 250 million characters		
Emulations	MT660/MT690, Epson FX+, IBM ProPrinter, XL, Genicom ANSI, HP2564C, Printronix P600/P6000, DEC LG01, Tally industrial graphics, contextual Arabic		
Interfaces - Standard	IEEE 1284 compliant parallel, serial with 38.4K baud transfer		
Interfaces - Optional	Twinax and coax (+IPDS), LANPlex, Ethernet (+IPDS)		
Noise level	52db(A)		
Power supply	Auto ranging: 90-130V and 180-264V Frequency 57-63Hz and 47-53Hz		
Power consumption	215W average		
Weight	83.92Kg (shipping weight 96.16Kg)		
Dimensions	1016(h) x 716(w) x 719(d)mm		

NB: Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.



Rutherford Road, Basingstoke,
Hampshire, RG24 8PD.
Tel: UK 0800 652 4557
International: +44 (0) 1256 481 521
Fax: UK 0870 872 2889
Web: www.tallygenicom.co.uk