

# T9114/T9114N

## Low cost laser performance for the home or office



The T9114 high performance laser printers represent a whole new dimension in affordable laser performance for the home or the office. With speeds of 14 pages per minute and print quality at 1200 dpi, these printers produce excellent output at a very low cost.

Choose the T9114N desktop laser printer with optional 550-sheet lower feed unit for additional paper tray input, and standard Ethernet 10/100 BaseT. With standard PCL6, the T9114 laser printer family allows you to easily upgrade to numerous available options without breaking your wallet.

The Plug and Play CD makes installation almost automatic and acts as a complete, single source of information about your new printer. The CD auto-senses your Windows operating system and installs the appropriate driver for your printer. You can choose to install only the driver for local printing or have the CD install the utilities to install, monitor and manage your printer on a network.

### **Mono Laser**

Colour Laser

Production Ink

Dot Matrix

Line Matrix

Consumables

- Superior performance at 14 pages per minute (A4)
- High monthly workload up to 15,000
- Standard Ethernet 10/100 Base-T connectivity (N version)
- Robust processor for speedy generation of documents
- Impressive paper handling with maximum input capacity of 1200 sheets for less interruption
- Rugged compact design
- No fuss printer driver for easy installation
- Excellent cost of operation

# T9114/T9114N

## Features & Specifications

### Mono Laser Printer

<b>Printing Technology</b>	Laser
<b>Processor</b>	66 Mhz 32 Bit RISC
<b>Print Speed - Mono</b>	Up to 14 pages per minute
<b>Monthly Workload - Average</b>	2,500 - 4,000 pages
<b>Max</b>	15,000 pages ( one time peak use )
<b>Print Resolution - Max</b>	600 x 600 dpi
<b>Memory - Standard</b>	4 Mb - T9114 12Mb - T9114N
<b>Emulation - Standard</b>	PCL6 including PCL5e/Epson FX
<b>Emulation - Optional</b>	PostScript Level 3 PDL ( T9114 only )
<b>Fonts</b>	1 Bit Map and 45 scaleable, 39 Barcodes OCR B and PDL ( T9114N only )
<b>Paper handling input - Standard</b>	Manual feed, 100 sheet multi-purpose feeder( MPF ) plus 550 sheet universal cassette ( based on A4 75gsm paper )
<b>Paper handling input - Optional</b>	2nd universal cassette accepts 550 sheets or 40 envelopes ( based on A4 75gsm paper )
<b>Paper handling output - Standard</b>	100 sheet face up rear feed ( straight paper path ) 250 sheet face down stacker ( based on A4 75gsm paper )
<b>Print media type</b>	MPF - paper, transparencies, labels, heavy paper stock, envelopes Standard cassette - paper Optional cassette - paper and envelopes
<b>Paper sizes</b>	MPF - A4, Letter, Legal, Folio, Executive, B5 Standard cassette - A4, Letter, Legal, Folio, Executive, B5 Optional cassette - A4, Letter, Legal, Folio Executive, B5
<b>Envelope sizes ( MPF and Optional Cassette )</b>	Monarch, COM 10, #9 C5, B5 Env, DL
<b>Non-printable area</b>	4mm from each edge / envelopes - 10mm from each side
<b>Media weight</b>	Cassette - 60-105gsm MPF - 60 - 163gsm
<b>Printer drivers</b>	Windows 95, 98, Win NT 4.0, Win 2000 & XP with N-UP, Forms Overlay, Booklet, Watermark and Manual Duplex printing. PPD file for PostScript PDL Level III for Windows and MAC
<b>Interfaces - Standard</b>	Parallel (Bi-directional IEEE 1284 compliant ECP/Nibble/Byte Mode) USB (Rev 1.0 compliant 12Mbps with ADT) Internal Ethernet 10BaseT & 100BaseT (T9114N only)
<b>Interface intelligence</b>	Automatic Interface Switching
<b>First page print time</b>	14 secs or less
<b>Warm-up time</b>	Less than 40 secs
<b>Acoustic level (ISO 7779)</b>	Printing - 48dBA Standby - 35dBA Sleep Mode - Background level
<b>Power consumption</b>	Energy Star Compliant, Average: 300W Standby: 70W Sleep Mode: 20W
<b>Weight</b>	12.4Kg (with consumables)
<b>Dimensions</b>	361(w) x 409(d) x 294(h) mm
<b>Input Voltage</b>	220 - 240V 50/60Hz
<b>Operating Environment - Temperature</b>	10°C - 30°C
<b>Operating Environment - Humidity</b>	20% - 80% relative humidity, non condensing
<b>MTBF</b>	50,000 pages ( Power on 8hr/day in recommended duty cycle )
<b>MTTR</b>	30 minutes
<b>Consumables</b>	Starter process unit - 3,000 pages* Replacement process unit - 6,000 pages* (*Based on 5% coverage of A4 page )
<b>Options</b>	2nd cassette ( 550 sheet or 40 envelopes ), PostScript Level 3 PDL ( T9114 only ), 16/32/64 Mb Memory, Internal - Ethernet 10BaseT & 100BaseTx ( T9114 only), Barcode Emulation ( T9114 only )

**NB: Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.**



Rutherford Road, Basingstoke,  
Hampshire, RG24 8PD.  
Tel: UK 0800 652 4557  
International: +44 (0) 1256 481 521  
Fax: UK 0870 872 2889  
Web: [www.tallygenicom.co.uk](http://www.tallygenicom.co.uk)